

	HDG Brugsvandsvandsbeholder Type RS	Datablad	
		Udgave 09/2009	HDG Bavaria GmbH D-84323 Massing Tel. +49 (0) 8724 / 897-0 www.hdg-bavaria.com

		150	200	300	400	500	750	1000
Generelle data								
Tankindhold	l (ca.)	152	197	310	398	490	750	1000
Vægt (tom)	kg	70	80	135	173	195	230	330
Ydelsesfaktor		2,9	4,0	9,8	14,5	18,9	24	30
Kontin. ydelse varmtvand 45°C/90°C	l/h (kW)	650 (26,5)	650 (26,5)	1220 (49,6)	1340 (54,5)	1746 (71)	2160 (88)	2425 (99)
Kontin. ydelse varmtvand 60°C/90°C	l/h (kW)	387 (22,6)	387 (22,5)	725 (42,1)	800 (46,5)	1036 (60,2)	1036 (60,2)	1440 (83)
Maks. varmevekslerydelse	kW	27	27	50	55	71	88	99
Maks. temperatur BV / VK	°C	95 / 130	95 / 130	95 / 130	95 / 130	95 / 130	95 / 130	95 / 130
Maks. tryk BV / VK	bar	10 / 16	10 / 16	10 / 16	10 / 16	10 / 16	10 / 16	10 / 16
Varmevekslerindhold	l	5,3	5,3	8,6	10,5	14	18	24
Varmevekslerflade nederst / øverst	m ²	0,8	0,8	1,45 / -	1,64 / -	2,1 / -	2,7 / -	2,9 / -
Behov centralvarmevand	m ³ /h	2	2	2,5	2,5	3	3,7	5
Tryktab i varmeveksler	mbar	75	75	139	146	277	340	245
Isolering	mm	50-PUR	50-PUR	55-PUR	55-PUR	55-PUR	100-WS	100-WS
Varmetab	kWh/24h	1,4	1,6	1,8	2,3	2,6	3,9	4,4
Tankdiameter med isolering	I mm	520	520	660	710	710	950	1100
Tankdiameter	H mm	-	-	-	-	600	750	900
Højde koldt vandstilslutning	A mm	120	120	215	250	252	280	180
varmt vandstilslutning	E mm	1135	1452	1265	1420	1722	1610	1760
Højde cirkulation	C mm	517	517	675	725	802	830	1040
Tankhøjde	F mm	1265	1582	1550	1700	1980	1990	2010
Kipmål	mm	-	-	1680	1840	2100	1980	2000
Højde centralvarme fremløb	D mm	632	632	775	825	902	930	950
Højde centralvarme returløb	B mm	120	120	290	330	330	280	320
Højde flange	G mm	317	317	300	335	335	400	447
Højde tømmemuffe	mm	-	-	-	-	-	980	1040
Højde muffe 1 til termostat	mm	372	372	360	395	397	-	-
Tilslutninger								
Koldt vand / varmt vand	DN (nip)	20 / 20	20 / 20	25 / 25	25 / 25	25 / 25	32 / 32	40 / 40
Cirkulation	DN (nip)	20	20	20	20	20	20	20
Centralvarme fremløb / returløb	DN (mf)	25 / 25	25 / 25	25 / 25	25 / 25	25 / 25	25 / 25	32 / 32
Tømmemuffe	DN (mf)	-	-	-	-	-	40	40
Udluftning	DN (mf)	20	20	-	-	-	15	15
Flange	NW	100	100	116	116	116	205	205
Følerrør	DN (mf)	15	15	15	15	15	-	-
Termometer (muffe)	DN (mf)	15	15	15	15	15	15	15
Anode	DN (mf)	20	20	25	25	32	32	32



HDG Brugsvandsvandsbeholder Type RS

Datablad

Udgave 09/2008

HDG Bavaria GmbH
D-84323 Massing
Tel. +49 (0) 8724 / 897-0
www.hdg-bavaria.com

Snitbillede af HDG brugsvandsbeholder type RS

